



MATERIAL SAFETY DATA SHEET **MSDS**

LYCON Inc.

MORTAR TECHNOLOGIES
Block Fill Grout, Fine & Coarse

Page 1 of 3

SECTION I PRODUCT AND COMPANY IDENTIFICATION

Manufacturer

LYCON Inc.

1110 Harding Street
Janesville, WI 53547

Telephone Number: 877-599-5090

FAX Number: 262-644-4011

Web www.lyconinc.com

Product Name: MORTAR TECHNOLOGIES BLOCK FILL GROUT, FINE & COARSE

Date Prepared: March 1, 2007

EMERGENCY PHONE NUMBER (608) 754-7701

SECTION II HAZARDOUS INGREDIENTS / IDENTITY INFORMATION

Hazardous Components	CAS #	OSHA PEL	Hazard Limits
Portland Cement	65997-15-1	5 mg/m ³	(respirable dust)
Fly Ash			
Silica Aggregates	14808-60-7	0.1 mg/m ³	(respirable dust)

SECTION III PHYSICAL / CHEMICAL CHARACTERISTICS

Boiling Point: N/A **Specific Gravity (H₂O = 1):** 2.60

Vapor Pressure (mm Hg.): N/A **Melting Point:** N/A

Vapor Density (AIR = 1): N/A **Evaporation Rate:** N/A

(Butyl Acetate = 1)

Solubility in Water: Slight

Appearance and Odor: Gray powder

SECTION IV FIRE AND EXPLOSION HAZARD DATA

Flash Point (Method Used): N/A **Flammable Limits:** N/A **LEL:** N/A **UEL:** N/A

Extinguishing Media: N/A

Special Fire Fighting Procedures: N/A

Unusual Fire and Explosion Hazards: N/A



MATERIAL SAFETY DATA SHEET *MSDS*

LYCON INC.

MORTAR TECHNOLOGIES
Block Fill Grout, Fine & Coarse

Page 2 of 3

SECTION V REACTIVITY

Stability: Stable

Conditions to Avoid: Moisture, will harden

Incompatibility (Materials to Avoid): Silica will dissolve in hydro-fluoric acid and produce gas

Hazardous Decomposition or Byproducts: NONE

Hazardous Polymerization: Will Not Occur

Conditions to Avoid: NONE known

SECTION VI HEALTH HAZARD DATA

Route(s) of Entry: **Inhalation:** YES **Skin:** YES **Ingestion:** NO

Health Hazards (Acute and Chronic):

Cement when combined with body moisture and wet cement, especially as an ingredient in plastic (unhardened) concrete, can dry the skin and cause alkali burn. Cement dust can irritate the eyes and respiratory system.

Chronic: Cement dust can cause inflammation of the lining tissue of the interior of the nose and inflammation of the cornea. Hypersensitive individuals may develop an allergic dermatitis. Cement can contain hexavalent chromium. Alkaline nature of Portland cement may cause skin irritation.

Carcinogenicity: NTP? Silica dust is probable carcinogen from inhalation

IARC Monographs? Silica dust may be carcinogen if inhaled. Volume 68

OSHA Regulated? Not Regulated

Signs and Symptoms of Exposure: Skin irritation and mucous membrane irritation.

Medical Conditions Generally Aggravated by Exposure: Freshly mixed concrete grout or mortar may cause skin injury. Avoid contact with skin and wash exposed areas promptly with water.

Emergency and First Aid Procedures: If powder gets into eyes, rinse immediately and repeatedly with water and get prompt medical attention.

SECTION VII PRECAUTIONS FOR SAFE HANDLING AND USE

Steps to Be Taken in Case Material is Released or Spilled: Scoop up to collection containers.

Waste Disposal Method: Mix with water.

Precautions to Be taken in Handling and Storing: Keep containers closed. Protect from moisture.

Other Precautions: Avoid breathing dust.



MATERIAL SAFETY DATA SHEET *MSDS*

LYCON INC.

MORTAR TECHNOLOGIES
Block Fill Grout, Fine Coarse

Page 3 of 3

SECTION VIII CONTROL MEASURES

Respiratory Protection (Specify Type): NIOSH approved organic respirator in confined areas.

Ventilation: Mechanical (General) Good general ventilation.

Protective Gloves: Rubber Gloves

Eye Protection: Safety glasses with side shields, goggles.

Other Protective Clothing or Equipment: Long sleeved shirt and pants.

Work/Hygienic Practices: Follow practices of good industrial hygiene.

N/A = Not Applicable

SECTION IX DISCLAIMER

THE INFORMATION IN THIS MSDS CONCERNING HEALTH HAZARD DATA WAS OBTAINED FROM SOURCES BELIEVED TO BE RELIABLE. HOWEVER, THE INFORMATION IS PROVIDED WITHOUT ANY REPRESENTATION OR WARRANTY, EXPRESSED OR IMPLIED, REGARDING ITS ACCURACY OR CORRECTNESS. ONCE THIS PRODUCT LEAVES OUR PLANT, THE CONDITIONS OR METHODS OF HANDLING, STORAGE, USE AND DISPOSAL OF THE PRODUCT ARE BEYOND OUR CONTROL AND MAY BE BEYOND OUR KNOWLEDGE. FOR THIS AND OTHER REASONS, WE DO NOT ASSUME RESPONSIBILITY AND EXPRESSLY DISCLAIM LIABILITY FOR LOSS, DAMAGE OR EXPENSE ARISING OUT OF OR IN ANY WAY CONNECTED WITH THE HANDLING, STORAGE, USE OR DISPOSAL OF THE PRODUCT.

OSHA's Hazardous Communication Standard
29 CFR 1910.1200

END OF MSDS DOCUMENT